

- Cleans, degreases and prepares surfaces for proper adhesion prior to painting.
- VOC compliant in US and Canada
- Odor free. Biodegradable.
- Replaces TSP/Acid Etch/TSP.



Clean and Prep Solution is used to clean and degrease while simultaneously dissolving mineral deposits, and increasing porosity for good adhesion on surfaces prior to painting. Can be used on painted surfaces,, bare plaster, concrete or fiberglass. VOC compliant, odor and fume free, water-rinse neutralize and it is biodegradable. Safe to use near plants or grass. Excellent for filter element cleaning.

PHYSICAL DATA	APPLICATION DATA	ASSOCIATED PRODUCTS
<p>COMPONENTS: 1 COVERAGE: 400—800 sq. ft/gal. contingent upon surface Non-photochemically reactive Self neutralizing OTC Compliant</p>	<p>METHOD: Brush, Airless or Conventional Spray. Wear Safety Goggles with side shields , rubber gloves and protective footwear . APPLICATION TEMP: 50° F. Min.</p>	<p>DS Acrylic Pool Paint Aqualuster Acrylic Pool Paint EP High Build Epoxy Pool Paint EP Epoxy Pool Paint A-2 Premium Rubber Pool Paint Type A-Chlorinated Rubber Pool Paint Pro 2000 Chlorinated Rubber Pool Paint Acrylic Deck Coat Wood Deck Stain Durathane Caulk Sealant Ramuc Thinner Skid-Tex Non Slip Additive</p>



Clean and Prep Solution

APPLICATION INFORMATION

Important: Read all instructions thoroughly before use. Wear safety goggles with side shields, rubber gloves and protective footwear.

Limitations: Do not apply to concrete that has already been sealed or stained.

Surface Preparation: After all surface repairs, power wash loose material off to a tight surface.

For Bare Concrete, Gunite, Marcite, or Plaster: Mix 1 gallon of Clean and Prep Solution with 2 gallons of water. Cleans approximately 400 square feet.

For Painted Surfaces or Bare Fiberglass: Mix 1 gallon Clean and Prep Solution with 5 gallons of water. Cleans approximately 600—800 square feet. Use garden sprayer for even application of product. Be sure the heavily soiled areas (such as waterline, steps or regular footpaths on concrete decks) are scrubbed well. Triple-rinse the surface with a strong stream of clean water while scrubbing to ensure complete removal of all material.

For Pool Filter Elements: Mix 1 gallon of Clean and Prep solution to 5 gallons of hot water; soak for at least 1 hour, rinse and repeat if necessary to completely remove scum and mineral deposits.

Clean Up & Storage: Clean all application tools with water immediately after use. Keep product from freezing—do not store at temperatures below 50° F.

Guarantees/Warranties: RAMUC DOES NOT MAKE NOR DOES IT AUTHORIZE ANYONE TO MAKE ANY WARRANTY OF MERCHANTABILITY OR FITNESS OR ANY PURPOSE or any other warranty, guarantee or representation expressed or implied, concerning this material except that it conforms to produce specifications distributed by the company. In any event, liability is limited to the replacement of product or its value, if proven to be defective in manufacturing.

Caution: Contains Phosphoric Acid. Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches or dizziness, increase fresh air or wear respiratory protection. (NIOSH/MSHA TC23C or equivalent.) or leave the area. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage.

First Aid: In case of eye contact, flush thoroughly with large amounts of water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. In case of respiratory difficulty, provide fresh air and call a physician. If swallowed, do not induce vomiting. Give one or two glasses of water and get medical attention immediately.

DO NOT TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN.