

**RAMUC®**



**RAMUC THINNER 1 US GAL**

Version 2.

Print Date 04/08/2009

REVISION DATE: 04/03/2009

**SECTION 1 - PRODUCT IDENTIFICATION / PREPARATION INFORMATION**

**Product Information**

Trade name : RAMUC THINNER 1 US GAL  
Product code : 9221000M01C  
  
Supplier : Republic Powdered Metals  
2628 Pearl Road  
Medina, OH 44256  
  
Telephone : (800) 551-7081  
Emergency Phone: : After Hours: Chemtrec 1-800-424-9300  
  
Product use : Coating

**Preparation Information**

Prepared by: : Rich Mikol  
Date: : 04/03/2009  
Telephone : (216) 292-5000 8:30 - 5:00 EST

**SECTION 2 - HAZARDS IDENTIFICATION**

**Emergency Overview**

Clear. Liquid. May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

**Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue.  
Eyes : Vapor and/or mist may cause eye irritation. Direct contact may cause temporary redness and discomfort.  
Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.  
Skin : May cause moderate irritation.

**Aggravated Medical Conditions**

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

**Chronic Health Effects**

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Prolonged or repeated exposure to xylene may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, heart muscle sensitization and arrhythmia, hearing loss, and brain, liver, kidney damage. Xylene overexposure may affect fetal development. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

**Target Organs:** Skin, Eye, Lung, Liver, Kidney, Nerve, Reproductive

**RAMUC®**



**RAMUC THINNER 1 US GAL**

Version 2.  
REVISION DATE: 04/03/2009

Print Date 04/08/2009

**SECTION 3 : HAZARDOUS INGREDIENTS**

Chemical Name	CAS-No.	Weight % Range
Xylene	1330-20-7	> 60.0

The ingredients listed above are hazardous as defined in the controlled products regulation. (CPR).

**SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

- Inhalation : Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**SECTION 5: FIRE / EXPLOSION HAZARDS**

- Flash point : 82.5 °F, 28 °C
- Method : Tag Closed Cup
- Lower explosion limit : 1.00 %(V) Solvent
- Upper explosion limit : 7.00 %(V) Solvent
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Smoke, fumes. Carbon monoxide and carbon dioxide can form. Nitrogen oxides can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water may be used to cool containers to minimize pressure build-up.
- Fire and explosion conditions : Vapor concentrations in enclosed areas may ignite explosively. Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flashback. Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors.

**RAMUC®**



**RAMUC THINNER 1 US GAL**

Version 2.  
REVISION DATE: 04/03/2009

Print Date 04/08/2009

**SECTION 6 - SPILLS / LEAKS / ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

**SECTION 7 - HANDLING AND STORAGE**

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Keep container closed when not in use. Vapor may migrate to sources of ignition. Do not smoke, weld, generate sparks, or use flame near container. Store in sealed containers in a cool, dry, ventilated warehouse location.

**SECTION 8 - PREVENTIVE MEASURES/EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Personal protection equipment**

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Protective measures : Use professional judgment in the selection, care, and use. Inspect and replace equipment at regular intervals.
- Engineering measures** : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

**Exposure Limits**

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Xylene	1330-20-7	Ontario TWA: Ontario STEL: ACGIH TWA: ACGIH STEL:	435 mg/m3 650 mg/m3 100 ppm 150 ppm	

**SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Physical State : Liquid

**RAMUC®**



**RAMUC THINNER 1 US GAL**

Version 2.

Print Date 04/08/2009

REVISION DATE: 04/03/2009

Form	:	Liquid
Color	:	Clear
Odor	:	Aromatic Solvent
pH	:	Not available.
Vapour pressure	:	Not available.
Vapor density	:	Heavier than air
Melting point/range	:	Not available.
Freezing point	:	Not available.
Boiling point/range	:	Not available.
Water solubility	:	Negligible
Evaporation Rate:	:	Not available.
Specific Gravity	:	0.868
% Volatile Weight	:	100 %

**SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid	:	Oxidizing agents.Strong acids.Strong bases.
Stability	:	Stable under normal conditions. Avoid welding arcs, flames or other high temperature sources.
Hazardous polymerization	:	Will not occur.

**SECTION 11 - TOXICOLOGICAL INFORMATION**

Xylene, CAS-No.: 1330-20-7	
Acute oral toxicity (LD-50 oral)	4,300 mg/kg ( Rat ) 1,590 mg/kg ( Mouse ) 6,670 mg/kg ( Rat ) 3,523 - 8,600 mg/kg ( Rat ) 5,627 mg/kg ( Mouse )
Acute inhalation toxicity (LC-50)	6,350 mg/l for 4 h ( Rat ) 3,907 mg/l for 6 h ( Mouse ) 8,000 mg/l for 4 h ( Rat )

**SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

**SECTION 13 - WASTE DISPOSAL CONSIDERATIONS**

RCRA Class	:	D001: Reportable Quantity = 100 lbs. (Characteristic of ignitability) This classification applies only to the material as it was originally produced.
Disposal Method	:	Dispose according to all applicable regulations (hazardous household waste depot, or as liquid industrial waste for industrial product).



**RAMUC THINNER 1 US GAL**

Version 2.  
REVISION DATE: 04/03/2009

Print Date 04/08/2009

**SECTION 14 - TRANSPORTATION / SHIPPING DATA**

**TDG / DOT Shipping Description:**

PAINT RELATED MATERIAL, 3, UN1263, PG III

**SECTION 15 - REGULATORY INFORMATION**

**North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**Canadian Regulations:**

WHMIS Classification : B2, D2A, D2B

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all of the information required by the CPR.

**Other Regulations:**

Regulatory VOC (less water and exempt solvent) : 868 g/l

**SECTION 16 - OTHER INFORMATION**

**HMIS Rating :**

Health	2
Flammability	3
Reactivity	0
PPE	

0 = Minimum  
1 = Slight  
2 = Moderate  
3 = Serious  
4 = Severe

**Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

**Prepared by: Sewnauth Raghunandan**

**Legend**

ACGIH - American Conference of Governmental Hygienists	OSHA - Occupational Safety and Health Administration
DOT - Department of Transportation	PEL - Permissible Exposure Limit
DSL - Domestic Substance List	RCRA - Resource Conservation and Recovery Act
EPA - Environmental Protection Agency	STEL - Short Term Exposure Limit
HMIS - Hazardous Materials Information System	TLV - Threshold Limit Value
IARC - International Agency for Research on Cancer	TSCA - Toxic Substances Control Act

**RAMUC®**



**RAMUC THINNER 1 US GAL**

Version 2.

Print Date 04/08/2009

REVISION DATE: 04/03/2009

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information System